

**PORTIONS
OF THIS
DOCUMENT
ARE
ILLEGIBLE**

LA-UR-80-1712

TITLE: TECHNIQUES WITH H^0 PRODUCED FROM POLARIZED H^- BEAMS

AUTHOR(S): Olin B. van Dyck, Andrew J. Jason, Daniel W. Hudgings

SUBMITTED TO: Fifth International Symposium on Polarization Phenomena in Nuclear Physics, to be held in Santa Fe, NM (August 11-15, 1980).

MASTER

DISCLAIMER
The U.S. Government is authorized to reproduce and distribute reprints for government purposes not withstanding any copyright notation that may appear hereon. This document is the property of the U.S. Government and is loaned to your organization; it and its contents are not to be distributed outside your organization.

By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes.

The Los Alamos Scientific Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy.

University of California



LOS ALAMOS SCIENTIFIC LABORATORY

Post Office Box 1663 Los Alamos, New Mexico 87545

An Affirmative Action/Equal Opportunity Employer

TECHNIQUES WITH H^0 PRODUCED FROM POLARIZED H^- BEAMS

Olin B. van Dyck, Andrew J. Jason, Daniel W. Hudgings
Los Alamos Scientific Laboratory, Los Alamos, NM 87545

I. INTRODUCTION

It is possible to perform useful manipulations by making H^0 beams from polarized H^- beams with stripper foils or stripping magnets (Sec. II). The hyperfine interaction (Sec. III) modifies the behavior of the proton polarization in H^0 , producing both useful and unwanted effects. Some depolarizing effects (Sec. IV) can be minimized.

II. STRIPPING

Foil Stripping. H^0 is created by H^- stripping in a thin layer of material and in turn is depleted by stripping to H^+ . In a layer of thickness t , neglecting direct $H^- \rightarrow H^+$ conversion,

$$\mu^0 \text{ fraction} = \frac{\lambda_-}{\lambda_0 - \lambda_-} (e^{-t/\lambda_0} - e^{-t/\lambda_-})$$

where λ_- = stripping length for $H^- \rightarrow H^0$, and λ_0 = stripping length for $H^0 \rightarrow H^+$. Thin plastic foils are convenient to use for strippers; approximate ($\pm 10\%$) values for stripping lengths¹ are $\lambda_- = 30 \mu\text{g}/\text{cm}^2$, $\lambda_0 = 60 \mu\text{g}/\text{cm}^2$. The maximum H^0 yield is about 50%.

Field Stripping. Stripping of relativistic H^- beams will occur from the rest-frame electric field $E = \eta cB$ produced by a transverse magnetic field B , where η = beam momentum/ H^- mass. Stripping length vs. field is plotted in Fig. 1, from the function fitted in a recent LAMPF experiment.²

The variable path length in the magnet, up to the point of H^- stripping, adds to the H^0 beam divergence in the bend plane. The fringe field produced by a simple square-edged 16 mm magnet gap added 1.6 mr (FWHM) to the 800-MeV beam divergence in the experiment of Ref. 2.

To preserve the beam polarization, H^- beams should enter the stripper magnet with polarization parallel to the field direction. The other components of the polarization tend to be lost. A conceivable application of a stripper magnet could be as a spin filter to reduce small unwanted components.

The polarization transfer in magnetic stripping of $H^- \rightarrow H^0$ was measured to be close to 100% (no loss measured at the 1% level). Possible depolarizing mechanisms are discussed below.

III. HYPERFINE INTERACTION

Zero-field Free Oscillation. In the initial H^0 beam, half the atoms have electron spin antiparallel to the proton spin. The hyperfine interaction causes the spins to trade orientation at the hyperfine frequency $f = 1.4$ GHz.¹ Consequently, the beam polarization oscillates between its maximum P_0 and 0: $P = P_0 (1 + \cos \omega t)/2$, $\omega = 2\pi f$ in the beam rest frame. In the laboratory, the beam has a polarization wavelength $\lambda = \hbar c/f$. At 800 MeV, $\lambda = 33$ cm.

Precession. If the applied magnetic field B is small with respect to the internal atomic field $B_0 = 506$ gauss, the H^0 system precesses as a unit having the magnetic moment of the electron and a spin of one. In a magnetic region of length L and transverse field B , the precession angle is $\theta = \mu_e BL/\hbar c$, $\mu_e = e\hbar/2m_e c =$ Bohr magneton. Thus the rate of H^0 precession is 330 times faster than H^\pm (in low fields). The free oscillation of polarization occurs independently of precession.

At intermediate fields, the observable effect is to give two-frequency precession.^{3,4} This is an added complication but can be treated without loss of polarization.¹

An H^0 polarization precessor system for accelerated H^- polarized beams can be built using small precessor magnets (50 gauss-meters) and either a foil or field stripper. After the H^0 precessor, the H^0 is stripped to H^+ at a maximum of the free oscillation. A demonstration system was reported previously.¹

Foil Stripping. H^{0*} made in impact stripping will quench to H^0 , adding an out-of-phase component to the already-freely-oscillating H^0 over several wavelengths, and producing a partially-depolarized component.

If the process $H^- \rightarrow H^0 \rightarrow H^+$ occurs within a distance \ll free oscillation wavelength, then loss of polarization does not occur either from free oscillation or H^{0*} production. Thus complete $H^- \rightarrow H^+$ stripping in a single foil, which is largely a two-step process, does not depolarize.

Field Stripping. In the central field region of the stripping magnet ($\sim 1.4T$), the free oscillation is absent. In the exit fringe field, the atom goes from high-field to low-field conditions, passing from free-spin to coupled-spin conditions. Thus the origin of the free oscillation is smeared along the beam axis. This process, however, is coherent or quantum reversible; the polarization can be recovered in a downstream field region, as shown in Fig. 2. Furthermore, if

the stripper magnet exit fringe field falls sufficiently rapidly, the depolarization can be made small. In the polarization transfer experiment, calculation showed 1.5% expected coherent depolarization. Zero depolarization was measured with about this accuracy (1%).

IV. REFERENCES

1. O. van Dyck, IEEE NS-26, p. 3992 (1979).
2. A. Jason et al., to be published.
3. A. Schenck, Nuclear and Particle Physics at Intermediate Energies, p. 181 (1975).
4. J. H. Brewer et al., Muon Physics, Vol. III, p. 30 (1975).




Fig. 1. H^- stripping length ($1/e$) vs. transverse magnetic field at 800 MeV, from Ref. 2





Fig. 2. H^0 polarization (upper graph) along beam axis Z , with coherent depolarization and repolarization in two 1-m, 300 gauss, magnetic field regions (shaded) parallel to polarization.



AMERICAN INSTITUTE OF PHYSICS

335 EAST 45 STREET, NEW YORK, NEW YORK 10017 · (212) 661-9404

TRANSFER OF COPYRIGHT AGREEMENT

Copyright to the article entitled

"Techniques With H^0 Produced From Polarized H^- Beams"

by

Olin B. van Dyck, Andrew J. Jason, Daniel W. Hudgings, Los Alamos Scientific

All Authors

Laboratory, Los Alamos, NM
87545

is hereby transferred to the AIP (to the extent transferable* under applicable national laws), effective if and when the article is accepted for publication in AIP Conference Proceedings.

However, the authors reserve the following rights:

- (1) All proprietary rights other than copyright such as patent rights.
- (2) The right to grant or refuse permission to third parties to republish all or part of the article or translations thereof. In the case of whole articles, such third parties must obtain AIP's written permission as well. However, such permission will not be refused by AIP except at the direction of the author. AIP may grant rights with respect to entire volumes.
- (3) The right to use all or part of this article in future works of their own, such as lectures, lecture notes, press releases, reviews, text books, or reprint books.
- (4) In the case of a "work made for hire," the right of the employer to make copies of the article for his own use, but not for resale.

To be signed by at least one of the authors (who agrees to inform the others, if any) or, in the case of a "work made for hire," by the employer.

Signature

OLIN B. van DYCK

Print Name

Title, if not Author

Univ. of California/Los Alamos Scientific Laboratory

Institution or Company

6/16/80

Date

The signed statement must be received by the Conference management before the manuscript can be accepted for publication.

*An author who is a U.S. Government officer or employee and prepared the submitted article as part of his or her official duties does not own any copyright in it. If at least one of the authors is not in this category, that author should sign above. If all the authors are in this category check the box here and return this form unsigned ☐